

# GIS-6000A



# GCS-1



## Shrink Fit Machine

**SFT**

## Cooling System

**SFT**

\* Automatically aligns tool holder with the induction head.

Model	<b>GIS - 6000A</b>
Power	220V, 18A, 1 phase
Cooling	Compressed Air 5 kg
Output power	6 Kw
Holder type	BT, HSK, CAT, SK
Clamping range	Φ3 ~ Φ16
Induction head travel range	Automatic Reset & Manual Reset
Heating time	User Setting
Maximum length of shrink fit chuck	300 mm
Shrinking time	3-18 seconds
Accessories	1. Toolholder Adapter : BT50 & BT40 * 1 each 2. Induction Ring : Φ3 - Φ6 mm * 1 pc Φ6 - Φ16 mm * 1 pc 3. BT40 Toolholder Adapter Clamp * 1
Dimension	410 x 520 x 740 mm (W*D*H)
Weight	30 kg

Model	<b>GCS - 1</b>
Power	220V, 18A, 2 phase
Cooling Time	30 seconds
Accessories	1. Tool Holder Adapter : BT50 * 2 pc & BT40 * 2 pc 2. Spray Cover * 1
Spray Cover Height	300 mm
Water Tank Volume	9L
Dimension	400 x 560 x 210 mm (W*D*H)
Weight	30 kg

**SFT** SF TECHNOLOGY CO.,LTD



No. 22, Aly. 53, Ln. 428, Sec. 3, Wenhua Rd., Rende Dist., Tainan City 71756, Taiwan (R.O.C.)  
T +886-6-270-3518 F +886-6-270-3510

www.sflinear.com.tw  
E-mail : sft@sftechnology.com.tw